




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : F04B 39/02	A1	(11) International Publication Number: WO 00/01949 (43) International Publication Date: 13 January 2000 (13.01.00)
<p>(21) International Application Number: PCT/EP99/03867</p> <p>(22) International Filing Date: 4 June 1999 (04.06.99)</p> <p>(30) Priority Data: PN98U000036 1 July 1998 (01.07.98) IT</p> <p>(71) Applicant (for all designated States except US): ZANUSSI ELETTROMECCANICA S.P.A. [IT/IT]; Via Giardini Cattaneo, 3, I-33170 Pordenone (IT).</p> <p>(72) Inventors; and (75) Inventors/Applicants (for US only): DELLBY, Fredrik [SE/SE]; Johan Skyttes Vag 226, S-125 34 Alvsjo (SE). ZONTA, Carlo [IT/IT]; Via L. Bianchi, 4, I-30035 Mirano (IT).</p> <p>(74) Agents: GIUGNI, Valter et al.; Propria S.r.l., Via Mazzini, 13, I-33170 Pordenone (IT).</p>		<p>(81) Designated States: BR, CN, JP, MX, SI, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published With international search report.</p>

(54) Title: OIL PUMP FOR A HERMETIC COMPRESSOR



(57) Abstract

Hermetic refrigeration compressor for household and similar refrigeration appliances, comprising a sealed casing (12), whose bottom (10) forms a sump for the lubricating oil (14), in which there are housed both the actual compressor and the related driving motor (16) which share a hollow crankshaft (20) rotating about a vertical axis, pumping means (34, 36) for the lubricating oil being connected to the lower end portion of said crankshaft. Said pumping means comprise a sleeve (34), which is rigidly fixed at the lower end portion of the crankshaft (20), and a piston member (36) which is elastically connected to the stator (22) of the motor (16) and floats freely inside said sleeve.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

OIL PUMP FOR A HERMETIC COMPRESSOR

5

10

DESCRIPTION

15

The present invention refers to a hermetic refrigeration motor compressor unit, in particular for use in household-type refrigeration appliances.

The actual refrigeration compressor (which is usually of the reciprocating or
20 rotary type) and the related electric driving motor are generally known to have a common shaft and to be enclosed in a sealed casing. Owing to the resulting impossibility for any kind of maintenance to be carried out subsequently, it is imperative for an effective, continuous and reliable lubrication of the moving parts of such a hermetically sealed unit to be assured throughout the operating life span,
25 which may amount to as many as more than 15 years, of the refrigeration appliance in which such a unit is mounted.

To this purpose, the hermetic motor compressor unit comprises means that are adapted to ensure, during the operating periods thereof, an adequate flow of the
30 oil that is filled in an appropriate quantity in the sealed casing at the end of the compressor manufacturing cycle, in such a manner as to enable it to not only lubricate said moving parts, but also prevent them from overheating.

It is a generally known practice for the above mentioned means to be provided
35 in the form of a downward extension of the shaft, that is longitudinally bored and shaped so as to be capable of drawing in the oil from the bottom of the sealed

casing and diffusing it, substantially by centrifugal effect, into the parts to be lubricated. Such a construction is usually effective in the case of traditional hermetic motor compressor units that are equipped with a single-phase two-pole induction motor operating at 2700 to 3000 rpm.

5

However, hermetic motor compressor units are increasingly being used since a few years now, which are equipped with electric direct-current brushless motors that are capable of operating at adjustable speeds varying from a maximum that may reach as many as 4000 rpm to a minimum that may on the contrary be as low
10 as 1000 rpm or even less, to the purpose of optimizing the performance of the related refrigeration appliance, particularly from an energy usage point of view.

Hermetic motor compressor units are also known which are equipped with a four-pole induction motor operating at a speed of only 1500 rpm so that, for a same
15 refrigeration capacity or output, a greater displacement of the compressor is needed.

In both above cited cases, the traditional lubrication and cooling means as the afore mentioned ones are largely inadequate owing to the fact that the low rotational speeds of the shaft do not ensure any adequate delivery head and flow rate of the oil sucked in from the bottom of the sealed casing, or a thorough diffusion of the same oil to all parts that need to be lubricated.

In a hermetic motor compressor unit in which the electric driving motor is
25 arranged below the compressor, it has been proposed that a worm-screw member be inserted with a slight radial gap in the hollow shaft starting from the lower end thereof (see document WO 96/29516). The relative movement between the shaft and the worm-screw member, which extends along the entire electric driving motor and is retained by a support being fixed to the stator of the motor,
30 ensures the desired oil flow. This solution has however a drawback in that the helical insert is completely contained inside the shaft and is affected by the heat transmitted by the motor. As a result, mutual expansions tend to take place during the operation of the motor compressor unit, which cause the radial gap between

the insert and the shaft to be altered, under corresponding variations in the lubrication performance.

It has been also proposed that a pumping chamber with a worm-screw member attached protrudingly to the lower end portion of the shaft and a therewith associated stationary sleeve (see documents WO 93/22557 and EP-A-0 728 946) be provided in the motor compressor unit. This kind of solution causes a further radial gap to be created between the stationary sleeve and the inner surface of the rotating shaft, so that leakages unavoidably take place owing to oil seeping through said gap, with the result of a reduced flow rate of the oil being pumped. Furthermore, a solution of this kind proves quite difficult and expensive to implement, since care shall duly be taken to ensure, between the two component parts of the pumping chamber, not only the afore mentioned circumferential gap, but also a gap on the horizontal plane between the sleeve and the lower end portion of the shaft in view of preventing said parts from undergoing a wear-down effect brought about by friction during operation.

It therefore is a main purpose of the present invention to provide, through the use of simple, reliable and low-cost means, an improved hermetic motor compressor unit that is capable of ensuring an effective oil flow even at operating speeds thereof that may be as low as approx. 800 rpm.

As this will be better explained further on, this and further aims are reached in a hermetic motor compressor unit provided with an oil suction arrangement featuring the characteristics as recited in the appended claims.

Anyway, such features, along with the advantages of the present invention, will be more readily understood from the description that is given below by way of non-limiting example with reference to the accompanying drawings, in which:

- Figure 1 is a cross-sectional view along a vertical plane of the lower portion of a hermetic motor compressor unit comprising the oil suction arrangement according to the present invention, in a first embodiment thereof;

- Figure 2 is a similar view as the one illustrated in Figure 1, but showing only the oil suction arrangement in a second embodiment thereof;

- Figure 3 is an exploded view of the component parts of the oil suction
5 arrangement shown in Figure 2.

With reference to Figure 1, it can be noticed that the items and details of the hermetic motor compressor unit that are of no relevance to the purposes of the present invention, starting from the actual compressor, are not shown since
10 considered to be largely known to all those skilled in the art.

A metal sealed casing 10 has a lower portion 12 that forms the sump in which the oil 14 collects which, filled in during compressor manufacturing, ensures the lubrication of the moving parts of an electric driving motor 16 and a compressor
15 situated thereabove that may for instance be of the reciprocating type.

In this particular embodiment, the motor 16 is of the direct-current brushless type with a permanent-magnet rotor 18 fixed to a vertical hollow shaft (which is common to the compressor situated thereabove) and a similar stator 22. The lower
20 portion of the stator comprises a shroud 24 that supports (with the aid of a pair of slots that are not shown in the Figure for reasons of greater simplicity) the end portions 26 and 28 of a bracket 30 that is preferably made out of spring-steel rod. As it can be noticed, this bracket 30 is substantially in the shape of a U with a recessed central zone 32.

25

Fixed to the lower end portion of the hollow shaft 20 there is a sleeve 34 that extends further vertically into the sump 10 so as to be able to plunge into and draw from the lubrication oil collected therein. The sleeve 34 is adapted to rotate jointly with the hollow shaft 20.

30

Inserted inside the sleeve 34 there is an oil suction member 36 which is provided, on its outer surface, with a helical groove that advantageously extends throughout, ie. covers the entire length of the same member. This groove, by

cooperating with the inner wall of the sleeve 34, forms a channel ensuring the passage of the oil from the sump 10 to the interior of the shaft 20.

The sleeve 34 and the fluted member 36 are preferably made of plastic material, ie. a material with a lower heat conductivity than the one of the metal material used to make the hollow shaft 20 itself. This solution is clearly simpler and less expensive as far as both the construction itself and the assembly are concerned. It furthermore enables the problems associated to the mutual thermal expansion of the sleeve and the fluted member to be largely eliminated. Conclusively, the performance and reliability characteristics of the whole hermetic motor compressor unit are improved, according to the actual purpose of the present invention.

The fluted member 36 is sustained by the elastic bracket 30, whose central zone 32 inserts freely in a notch provided in the lower head portion of the member 36. This type of elastic assembly enables the member 36 to float, but not rotate, inside the sleeve 34 during the operation of the motor compressor unit, thereby enabling possibly occurring misalignments of the shaft 20 and the oil suction arrangement to be compensated for.

20

A second embodiment of the present invention, which is based on the same operating principle and ensures practically the same level of effectiveness as the afore described embodiment, is illustrated in Figures 2 and 3, in which the same reference numerals are used to indicated items and details corresponding to the ones illustrated in Figure 1. As a result, to the lower end portion of the shaft 20 there is again fixed a sleeve 34, in this case however via an extension 40 of the same shaft. In the sleeve 34 there is inserted a floating piston member 36 that is sustained by the elastic bracket 30 whose end portions 26 and 28 are connected to the shroud of the motor 16, as this is shown in Figure 1.

30

The construction-related difference lies in the fact that the floating member 36 (Figure 2) is provided in its outer surface with two axial and diametrically opposed recesses 42 that cooperate with corresponding apertures 44 and 54 which are

provided at respective at respective different levels and pass through the wall of the sleeve 34. Furthermore, a undulated cam-profiled spring washer 46 is mounted between the member 36 and the sleeve 34. This cam-profiled washer 46 is fixed to the sleeve 34, preferably by bonding, and is adapted to act against a cross
5 extension 56 that is provided at the lower end portion of the member 36. This extension 56 is in turn provided with a downward open notch, in which the elastic bracket 30 sustaining the oil suction arrangement is able to insert freely.

The attachment of the extension 40 to the shaft 20 (see Figure 2) is brought
10 about simply by press-fitting the two parts together, thanks to the ability of the upper end portion of the extension 40 to deform owing to the presence of a notch 48, as well as to a button 50 engaging a recess 52. The button 50 and the recess 52 are provided on the outer surface of the extension 40 and the inner surface of the shaft 20, respectively.

15

During the operation of the unit, when the shaft 20 rotates jointly with the extension 40 and the sleeve 34, the cam-profiled washer 46 acts against the extension 56 and pushes the piston-like member 36 downwards against the action of the elastic bracket 30 that tends to bias, ie. push the member 36 upwards. As a
20 result, thanks to the combined effect of the curvature of the washer 46 and the elasticity of the bracket 30, the rotation of the shaft 20 is able to bring about a reciprocating movement of the member 36 in a vertical direction.

The lubricating oil is drawn in from the oil sump into the recesses 42 of the
25 piston-like member 36 when the sleeve 34 is rotated into the position in which it allowsthe recesses 42 to communicate with the lower apertures 44. This occurs during the downstroke of the member 36. When the sleeve 34 is then rotated by an angle of approx. 90° with respect to the above mentioned position, the oil is able to flow from the recesses 42 through the upper apertures 54 into the hollow shaft 20.
30 This occurs during the upstroke of the member 36.

The described solution therefore constitutes an effective positive-displacement piston pump without moving valves.

5

CLAIMS

10 1. Hermetic motor compressor unit for household and similar refrigeration appliances, comprising a sealed casing (10), whose bottom (12) forms a sump for the lubricating oil (14), in which there are housed the actual compressor and the related driving motor (16) which share a common hollow crankshaft (20) rotating about a vertical axis, lubricating oil suction means (34, 36) being provided at the
15 lower end portion of said crankshaft, characterized in that said oil suction means comprise a sleeve (34), which is rigidly fixed to the lower end portion of the crankshaft (20) and in which a fluted member (36) is inserted that is connected elastically with the stator (22) of the motor (16), said oil suction means extending downwards fully outside said hollow shaft (20).

20

2. Hermetic motor compressor unit according to claim 1, characterized in that said sleeve (34) and said fluted member (36) are made of a material having a lower thermal conductivity than the material of which the hollow shaft (20) is made.

25 3. Hermetic motor compressor unit according to claim 1 or 2, characterized in that said fluted member (36) is sustained by a substantially U-shaped bracket (30) formed by a metal wire or strip, whose intermediate zone (32) engages the lower end portion of the fluted member, and whose side arms (26, 28) are anchored to the stator (22) of the electric motor (16).

30

4. Hermetic motor compressor unit according to any of the claims 1 to 3, characterized in that said fluted member (36) is a member that is provided on its

outer surface with a helical groove forming the channel for the compressor lubrication oil (14) to pass therethrough.

5 5. Hermetic motor compressor unit according to any of the claims 1 to 3, characterized in that said fluted element (36) is a piston-like member that is provided on its outer surface with axial, mutually opposed recesses (42) that are adapted to cooperate with corresponding radial apertures (44, 54) provided at respective different levels and passing through the wall of said sleeve (34)..

10 6. Hermetic motor compressor unit according to claim 5, characterized in that at the lower end portion of said sleeve (34) there is fixed a undulated cam-profiled spring washer (46) that cooperates with a cross extension (56) of said piston-like member (36).

15




FIG. 1





FIG. 2



INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 99/03867

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 F04B39/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 F04B F16N F04C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	DE 16 28 245 A (ETABLISSEMENTS BEAUDOUIN) 28 January 1971 (1971-01-28) page 3 - page 5 page 7 - page 14; figures 3,4 ---	1,3-5
Y	WO 93 22557 A (BRASIL COMPRESSORES SA ;KRUEGER MANFRED (BR); WAGNER NILSON (BR)) 11 November 1993 (1993-11-11) cited in the application page 8, line 6 - page 16, line 16; figures 3,4,6 ---	1,3-5
A	EP 0 728 946 A (ZANUSSI ELETTRODOMESTICI) 28 August 1996 (1996-08-28) cited in the application column 2, line 48 - column 4, line 28; figures 1-6 --- -/--	1

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
"E" earlier document but published on or after the international filing date
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
"O" document referring to an oral disclosure, use, exhibition or other means
"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

13 September 1999

Date of mailing of the international search report

20/09/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Jungfer, J

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 99/03867

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 3 388 855 A (AYLING ROBERT W ET AL) 18 June 1968 (1968-06-18) column 2, line 8 - line 44 column 3, line 7 - line 24; figures 1-3 -----	1-6
A	PATENT ABSTRACTS OF JAPAN vol. 009, no. 275 (M-426), 2 November 1985 (1985-11-02) & JP 60 119389 A (TOSHIBA KK), 26 June 1985 (1985-06-26) abstract -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 99/03867

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 1628245	A	28-01-1971	NONE	
WO 9322557	A	11-11-1993	CN 1079028 A,B	01-12-1993
EP 0728946	A	28-08-1996	IT PN950014 U	23-08-1996
US 3388855	A	18-06-1968	NONE	
JP 60119389	A	26-06-1985	NONE	